

CLSS PATHWAY POWER SUPPLY

A Dedicated Power Supply for Honeywell's Connected Life Safety Services (CLSS) Pathway

Honeywell's CLSS Pathway is a dual path, dual SIM, and dual listed digital fire alarm communicator compatible with any Honeywell or 3rd party fire alarm panel – supporting dialer capture or relay. [CLSS Pathway is your pathway to more connected buildings](#) – providing the latest technology in fire alarm communications helping to deliver faster, code compliant alerting to central monitoring stations, enable line of site monitoring for dealers and facility managers, and unlock access to automated test and inspection reporting.

The CLSS Pathway now has a dedicated power supply option available for applications where you do not have the option to use power from the fire alarm panel.

CLSS Pathway Power Supply (HW-AV-ENC2-PS) use cases include:

- POTS conversions
- Taking over the monitoring of a facility or campus
- Reducing risk of additional costs of upgrading the entire fire system

The CLSS Pathway Power Supply is designed to power the CLSS Pathway communicator in fire alarm systems. It provides regulated DC supply with integrated battery backup and fault monitoring. The unit complies with UL 864, UL2610, and other life safety standards. The Pathway Power Supply helps reduce risk in permitting process and installation liability.



12V power supply for applications requiring a dedicated power source



Supports mounting CLSS Pathway (HW-AV-LTE-M-2 - sold separately)



Supports (1) 12V battery at 7 Ah, 8 Ah or 8.5 Ah (sold separately)



Compatible with Fire-Lite lock & key (17044 & 17003 - sold separately)

Features and Benefits

- Output: 610mA @ 12 VDC - 15 VDC, charging: 8.5Ah maximum
- Mounting options for CLSS Pathway (HW-AV-LTE-M-2 sold separately)
- Bracket for standard 7Ah battery
- Two form C normally-energized relays - one for AC Status and other for all troubles like AC Fail, Battery Trouble, Charger Trouble, Communication path failures, and other general troubles
- Configurable AC trouble report delay (0hrs, 1hr) via jumper position
- Diagnostic LEDs visible from exterior
- Double knockouts and removable door for ease of installation and wiring
- Predrilled for tamper switch installation
- Includes antenna retaining bracket



The CLSS Pathway Power Supply includes a metal enclosure, integrated power supply, and mounting options for the CLSS Pathway*. This supports mounting the CLSS Pathway and (1) 12V battery at 7 Ah, 8 Ah, or 8.5 Ah. Antenna included with the CLSS Pathway may be mounted on top and secured with the included metal bracket.



CLSS PATHWAY POWER SUPPLY IS AVAILABLE NOW THROUGH WHOLESALE DISTRIBUTION CHANNELS.



Visit the CLSS Pathway page to learn more.
hwll.co/pathway